

# Rider Smallest auditorium Chassé Theater

Version 25-03-2026 (ENG)



## technical data

**Attention: as the small auditorium is situated on the first floor, the elevator must be used to transport the set. Maximum dimensions of set pieces: 4.6 m x 2,06 m (doors to auditorium)  
The inner dimensions of the lift door are W 3,0 m x H 2,10 m.**

### stage dimensions:

Stage (seating system fully extended)	wide 11.5m (between masking)	deep - 11 m
Stage (seating extended + 1 additional row)	wide 11.5m (between masking)	deep - 10,5 m
Stage (seating extended + 2 additional rows)	wide 11.5m (between masking)	deep - 9,75 m
Auditorium + stage (seating system fully retracted)	wide 14 m	deep 19.5 m
Backstage	wide 14 m	deep 1.63m
Behind cyclorama	high 2.85 m	
Light bridges	5 x	
	safe working load bridge	150 kg/m
	safe working load point hoists	250 kg
Height under light bridges	5.4 m	
Maximum floor pressure	500 kg/m <sup>2</sup>	

**fly bar system:**

Fly bars	5 electrically controlled (9M) + 2 lateral flybars eltrc.
Safe working load fly bar	200 kg in total
	100 kg between steel cables
Hight fly bar	Fly bar 1, 2, 4 & 5: 6.70m
	Fly bar 3 and 2 lateral flybars: 6.50m
Hall truss	1 electrically controlled (7M) above stand. Between hall bridges 1 and 2. Distance 6.30m from stage zero point to truss.
Maximum load hall truss	250 kg in total

**auditorium seating system:**

Telescopic seating system	190 seats (+8 @ FOH position)
	20 seats on first additional row
	20 seats on second additional row

**masking:**

Colour of masking	night blue
Legs / tabs	4 pairs
Cyclorama	off white (12m wide x 5.4 m high)
Fond	present
Side masking	can be created with the legs

**lighting:**

Lighting computer	Compulite Spark-Top, GrandMA DOT2, High End Systems Full Boar. Available on request.
Dimmers	ADB twin-tech. a total of 124 dimmers 12 of which 5kW all the rest 3 kW
DMX 512	operational from Control Room or auditorium
Remote Control	ELC Focus Brain
Follow spots	no spots present
Spots	various ADB profiles and PC 's, 1 kW
Cyclorama floods	15 x 1 kW ADB Cyclorama floods
free usable spots	various conventional and intelligent fixtures. Complete list on request.

**power supply:**

Power supply	1 x 125 Amp. 3 Fase 400V/ backstage stage R. 1 x 63 Amp. 3 Fase 400V/ backstage stage R.
--------------	---

**sound system:**

Sound system controlled by a Midas XL-88 matrix which controls several XTA 444 processors.

**P.A. System:**

Speaker brand	Adamson
Amplifiers	Lab Gruppen D80L
Processors	Lake LM44
	<i>Access to this system can be given on request.</i>

**setup:**

Groundsystem L&R	2 x Adamson IS7 + 2 x Adamson IS118 sub
Flown system L&R	4 x Adamson IS7

**the following sections can becontrolled separately:**

Array top left, Array top right, Array left stack, Array right stack, left sub low, right sub low

This auditorium has got a Soundcraft GB2R-12 mixing console mounted in Control Room.

**general information:**

Loading docks

Two of the 4 loading docks on the left side of the theatre have got a lift. The other two have a dockleveller.

As the small auditorium is situated on the first floor, the in-house elevator is needed for set transportation.

Maximum dimensions of set pieces 4.6 m x 2.06 m

The inner dimensions of the lift door are

W 3,0 m x H 2,10 m.

Dressingrooms

The small auditorium has 4 dressingrooms, 2 toiletgroups and 2 showers on it's stage level.

Stage door

At the left hand side, facing the theatre, next to the loading docks.

Information

For more information please contact our Backoffice.

tel: 0031 (0) 76 530 3 171

E-mail address: [backoffice@chasse.nl](mailto:backoffice@chasse.nl)

Internet address: [www.chasse.nl/techniek](http://www.chasse.nl/techniek)